



# EXEC Commands in Configuration Mode

---

## Feature History

Release	Modification
12.1(11b)E, 12.2(7)B, 12.2(7)PB, 12.0(20)SP, 12.0(20)ST, 12.0(21)S, 12.2(8)T	This feature (the <b>do</b> command) was introduced.

This document describes the EXEC Commands in Configuration Mode feature and contains the following sections:

- [Feature Overview, page 1](#)
- [Supported Platforms, page 2](#)
- [Supported Standards, MIBs, and RFCs, page 2](#)
- [Configuration Tasks, page 3](#)
- [Configuration Examples, page 3](#)
- [Command Reference, page 4](#)

## Feature Overview

You can now issue EXEC-level Cisco IOS commands (such as **show**, **clear**, and **debug** commands) from within any configuration mode (such as global configuration mode) by issuing the **do** command followed by the desired EXEC command.

## Benefits

This feature provides the convenience of entering EXEC-level commands without needing to exit the current configuration mode.



---

**Americas Headquarters:**  
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2007 Cisco Systems, Inc. All rights reserved.

## Restrictions

You cannot use the **do** command to execute the **configure terminal** EXEC command because issuing the **configure terminal** command changes the mode to configuration mode.

## Related Documents

- [Cisco IOS Configuration Fundamentals Command Reference](#)

## Supported Platforms

- This command is supported on all platforms running the software releases (and all derivative releases) listed in the Feature History at the beginning of this document.

### Determining Platform Support Through Cisco Feature Navigator

Cisco IOS software is packaged in feature sets that support specific platforms. To get updated information regarding platform support for this feature, access Cisco Feature Navigator. Cisco Feature Navigator dynamically updates the list of supported platforms as new platform support is added for the feature.

Cisco Feature Navigator is a web-based tool that enables you to quickly determine which Cisco IOS software images support a specific set of features and which features are supported in a specific Cisco IOS image. You can search by feature or release. Under the release section, you can compare releases side by side to display both the features unique to each software release and the features in common.

To access Cisco Feature Navigator, you must have an account on Cisco.com. If you have forgotten or lost your account information, send a blank e-mail to [cco-locksmith@cisco.com](mailto:cco-locksmith@cisco.com). An automatic check will verify that your e-mail address is registered with Cisco.com. If the check is successful, account details with a new random password will be e-mailed to you. Qualified users can establish an account on Cisco.com by following the directions at <http://www.cisco.com/register>.

Cisco Feature Navigator is updated regularly when major Cisco IOS software releases and technology releases occur. For the most current information, go to the Cisco Feature Navigator home page at the following URL:

<http://www.cisco.com/go/fn>

## Supported Standards, MIBs, and RFCs

### Standards

No new or modified standards are supported by this feature.

### MIBs

No new or modified MIBs are supported by this feature.

To obtain lists of supported MIBs by platform and Cisco IOS release, and to download MIB modules, go to the Cisco MIB website on Cisco.com at the following URL:

<http://www.cisco.com/public/sw-center/netmgmt/cmtk/mibs.shtml>

**RFCs**

No new or modified RFCs are supported by this feature.

## Configuration Tasks

See the following section for the configuration task for the EXEC Commands in Configuration Mode feature:

- [Executing an EXEC Command in Configuration Mode](#) (optional)

## Executing an EXEC Command in Configuration Mode

To execute an EXEC-level command in any configuration mode (including configuration submodes), issue the following command in global configuration mode or the mode from which you want to issue the EXEC command:

Command	Purpose
<pre>Router(config)# do command Router(config)#</pre>	<p>Allows you to execute any EXEC mode command from within any configuration mode.</p> <ul style="list-style-type: none"> <li>• <i>command</i>—The EXEC command to be executed.</li> </ul>
<p>or</p> <pre>Router(config-if)# do command Router(config-if)#</pre>	

## Configuration Examples

This section provides the following configuration examples:

- [Executing an EXEC Command in Configuration Mode Examples](#)

## Executing an EXEC Command in Configuration Mode Examples

The following example shows how to execute the EXEC-level **show interface** command from within global configuration mode:

```
Router(config)# do show interfaces serial 3/0

Serial3/0 is up, line protocol is up
  Hardware is M8T-RS232
  MTU 1500 bytes, BW 1544 Kbit, DLY 20000 usec, rely 255/255, load 1/255
  Encapsulation HDLC, loopback not set, keepalive set (10 sec)
  Last input never, output 1d17h, output hang never
  Last clearing of "show interface" counters never
.
.
.
Router(config)#
```

The following example shows how to execute the EXEC-level **clear vpdn tunnel** command from within VPDN configuration mode:

```
Router(config-vpdn) # do clear vpdn tunnel
Router(config-vpdn) #
```

## Command Reference

The following commands are introduced or modified in the feature or features documented in this module. For information about these commands, see the *Cisco IOS Configuration Fundamentals Command Reference* at

[http://www.cisco.com/en/US/docs/ios/fundamentals/command/reference/cf\\_book.html](http://www.cisco.com/en/US/docs/ios/fundamentals/command/reference/cf_book.html). For information about all Cisco IOS commands, go to the Command Lookup Tool at <http://tools.cisco.com/Support/CLILookup> or to the *Cisco IOS Master Commands List*.

- **do**

---

CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0711R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007 Cisco Systems, Inc. All rights reserved.